



Description

The TA1017 SISO Power Amplifier is a class AB GaN module with an operating frequency range of 1700 to 2400 MHz. Designed for both military and commercial applications, this amplifier features an input voltage range of +10 to +30 VDC and a saturated RF output power of +45 dBm. With the capability of supporting any signal type and modulation format, all in a low-SWaP package, this unit is ideal for applications where high power-density, efficiency, and linearity are key.

TABLE OF CONTENTS

- Product Features and Applications
- Characteristics and Specifications
- Power Supply Specifications
- Mechanical Specifications
- Interface Specifications
- Environmental Specifications
- Protections and Maximum Ratings
- DC and Control Connector
- Mechanical Drawing

Features

- Under Voltage Protection
- Temperature Monitor Output
- Over-Temperature Protection
- Forward Power Measurement

Applications

- Military or Commercial Radio Systems
- Unmanned Systems
- Vehicle Systems
- Aircraft Systems
- Fixed Site Infrastructure

CHARACTERISTICS & SPECIFICATIONS

Specifications subject to change without notice. Typical performance at 28VDC at 25°C in a 50Ω system.

Tx Specifications (Per Channel)

Parameter	Min.	Typ.	Max	Unit
Operating Frequency	1700	—	2400	MHz
64QAM Power Output 20 MHz BW, -27 dB EVM Limit	32	—	—	dBm
BPSK Power Output 20 MHz BW, -7 dB EVM Limit	44	—	—	dBm
Saturated Power Output CW Sweep at Design Limit	—	45	—	dBm
Small Signal Gain	25	27	—	dB
Small Signal Gain Flatness	—	—	3	dB (peak to peak)
Input Return Loss	—	—	-12	dB
Tx Switching Time	—	1	2	μS

Power Supply Specifications

Parameter	Min.	Typ.	Max	Unit	Notes
Supply Voltage Range	10	28	30	VDC	—
RMS Operating Current Draw (Idle)	—	0.9	—	A	VDC Supply Voltage, Idle in Receive Mode
RMS Operating Current Draw (64QAM Power Output)	—	1.05	—	A	28VDC Supply Voltage, 802.11 WLAN Signal, 50% Duty Cycle
RMS Operating Current Draw (BPSK Power Output)	—	1.6	—	A	28VDC Supply Voltage, 802.11 WLAN Signal, 50% Duty Cycle

Mechanical Specifications

Parameter	Value	Unit
Dimensions (L x W x H)	4.925 x 2.533 x 0.7 (125.1 x 64.3 x 17.8)	in (mm)
Cooling	Baseplate Conduction	—
Weight	4 (113)	oz (g)

CHARACTERISTICS & SPECIFICATIONS (CONT.)

Specifications subject to change without notice.

Interface Specifications

Parameter	Value	Notes
RF Connectors (Input / Output)	SMA-F / SMA-F	—
Power / Signal Connector	MDM-15SH034B	Connector appearing on unit (Manufacturer P/N)
Mating Connector	M83513/03-B03C	Mating connector required for interfacing (Manufacturer P/N)
Test Integration Cable	CBL63	Triad P/N available for purchase separately

Environmental Specifications

Parameter	Min.	Max	Unit
Operating Temperature (Housing Temp.)	-40	85	°C
Storage Temperature	-55	85	°C
Altitude	0 (0)	30000 (9144)	ft. (m.)
Ingress Protection Rating	IP54		—
Shock / Vibration	Designed to comply with MIL-STD-810 Shock / Vibration Test Methods		—

Protections and Maximum Ratings

Parameter	Value	Unit	Notes
Maximum RF Input (Per Channel)	22	dBm	CW Power
Over Temp Protection Trip Level	85	°C	Internally Monitored System Temperature
RF Output Open Load Survivability	45	dBm	CW with Open Circuit at Antenna Port

DC / CONTROL CONNECTOR

Input and Output Pins

TTRM Connector Part Number			Mating Connector Part Number	
MDM-15SH034B			M83513/03-B03C	
Pin	Label	Type	I/O	Notes
1	Vin	Power	N/A	Supply Voltage - Range Specified in Data Sheet
2	Vin	Power	N/A	Supply Voltage - Range Specified in Data Sheet
3	Vin	Power	N/A	Supply Voltage - Range Specified in Data Sheet
4	FWD	Signal	Output	Forward Power Detector
5	AMP ENABLE	Signal	Input	TTL High or No Connection = Enable TTL Low = Disable
6	TEMP	Signal	Output	Temp Monitor Temp in DegC = (Vout - 0.5V) * 100
7	GND	Power	N/A	Power Supply Return (Ground)
8	GND	Power	N/A	Power Supply Return (Ground)
9	Vin	Power	N/A	Supply Voltage - Range Specified in Data Sheet
10	Vin	Power	N/A	Supply Voltage - Range Specified in Data Sheet
11	N/C	N/A	N/A	NO CONNECTION
12	SIG GND	Signal	N/A	Signal Ground
13	GND	Power	N/A	Power Supply Return (Ground)
14	GND	Power	N/A	Power Supply Return (Ground)
15	GND	Power	N/A	Power Supply Return (Ground)

Note: All +VDC and GND pins should be populated as shown.

MECHANICAL DRAWING





